

APPLICATION and PERFORMANCE SPECIFICATION

ACT1S8RS120N

- Line Voltage: 120V 60Hz
- Lamp End of Life Protection
- Rapid Start

Lamp Type			Min. Start Temp. (F/C)	Vin (V)	In (A)	Pin (W)	ATHD ≤%	PF ≥	CF ≤	BF	BEF
Type	No.	Watts									
* F8T5	1	8	0/-18	120	0.15	9.0	160	0.5	1.7	0.98	0.75
F6T5	1	6	0/-18	120	0.13	7.5	170	0.5	1.7	0.97	0.73
F4T5	1	4	0/-18	120	0.11	6.0	170	0.4	1.7	1.0	0.67

Note: Application and Performance Specification Information Subject to Change without Notification.

Performance

- Meets ANSI Standard C62.41-2002
- Meets FCC 18 CONSUMER Limits

Safety

- No PCB's
- UL & cUL listed (Class P, Type 1 Outdoor)
- 0CV 300V

Application

- Maximum Ambient Temperature: 131°F, 55°C
- Sound Rated: A
- Maximum case temperature Tc: 167°F, 75°C
- Starting time: $0.5s < t < 2s$

Physical Parameters

- Length 5.9" (150mm)
- Width 0.9" (23.7mm)
- Height 0.75" (19.1mm)
- Weight 0.26 lbs

Lead Length

- White/Black 7" ± 1"
- Blue 18" ± 1"
- Red 7" ± 1"

