

APPLICATION and PERFORMANCE SPECIFICATION

ACT1P400PSUNV

· Line Voltage:120-277V 50/60Hz

· Program Start

· Active Power Factor Correction

· Lamp End of Life Protection

· TYPE CC

Lamp Type		Min. Start Temp. (°F/°C)	Vin (V)	Iin (A)	Pin (W)	ATHD ≤%	PF ≥	CF ≤
Type	No.							
T5 UVC36"	1	-20/-29	120	0.48	58	10	0.98	1.70
T5 UVC30"	2	-20/-29	120	0.40	49	10	0.98	1.70
T5 UVC20"	3	-20/-29	120	0.26	32	10	0.98	1.70
T5 UVC16"	4	-20/-29	120	0.21	25	10	0.98	1.70
T5 UVC36"	5	-20/-29	277	0.21	58	10	0.98	1.70
T5 UVC30"	6	-20/-29	277	0.18	48	10	0.95	1.70
T5 UVC20"	7	-20/-29	277	0.12	31	15	0.95	1.70
T5 UVC16"	8	-20/-29	277	0.10	25	15	0.95	1.70

Note: the above data is tested at 60Hz.

Application and Performance Specification Information Subject to Change without Notification.

Performance

Meets ANSI Standard C82.11-2002

Meets ANSI Standard C62.41-2002

Meets FCC 18 Non-CONSUMER Limits

Safety

No PCB's, Type HL

UL listed (Class P, Type 1 Outdoor)

OCV : 300V

No-load Power : 0.2W

Application

Maximum Ambient Temperature: 131°F,55°C

Remote Mounting: 18 ft. max. Lead length, 18AWG

Sound Rated: A

Maximum case temperature Tc: 167°F,75°C

Physical Parameters

Length 9.75"/248mm

Width 1.5"/38mm

Height 1.2"/31mm

Mounting 8.9"/226mm

Weight 1.3 lbs

Lead Length

White, Black 18"(±1")

Red/ Blue 32"(±1")

APPLICATION and PERFORMANCE SPECIFICATION

