



APPLICATION and PERFORMANCE SPECIFICATION

ACT2S13PSUNV-C

- Line Voltage:120-277V 50/60Hz
- Series Lamp Operation
- Lamp End of Life Protection
- Program Start
- Active Power Factor Correction
- Type CC

Lamp Type			Min. Start Temp. (F/C)	V _{in} (V)	I _{in} (mA)	P _{in} (W)	ATHD ≤%	PF ≥	CF <	BF	BEF
Type	No.	Watts									
CFQ13W	2	13	0/-18	120	260	32	10	0.98	1.70	1.2	3.75
CFQ13W	1	13	0/-18	120	150	18	15	0.97	1.70	1.2	6.66
CFQ13W	2	13	0/-18	277	110	31	10	0.98	1.70	1.2	3.87
CFQ13W	1	13	0/-18	277	70	19	15	0.97	1.70	1.2	6.31

Note: the above data is tested at 60Hz. Application and Performance Specification Information Subject to Change without Notification.

UL&cUL is in application

Performance

- Meets ANSI Standard C82.11-2005
- Meets ANSI Standard C62.41-2002
- Meets FCC 18 Non-CONSUMER Limits

Safety

- No PCB's
- UL listed (Class P, Type 1 Outdoor)
- OCV 300V
- No-load Power :< 5W

Application

- Maximum Ambient Temperature: 131°F, 55°C
- Remote Mounting: 18 ft. max. Lead length, 18AWG
- Sound Rated: A
- Maximum case temperature T_c: 194°F, 90°C

Physical Parameters

- Length 5.05" 128.3(mm)
- Width 2.42" 61.4(mm)
- Height 0.9" 23.0(mm)
- Mounting 4.66" 118.4(mm)
- Weight 0.46 lbs / 210g

