



APPLICATION and PERFORMANCE SPECIFICATION

ACT1S40RS120N

- Line Voltage: 120V 60Hz
- Series Lamp Operation
- Rapid Start
- Lamp End of Life Protection

Lamp Type			Min. Start Temp. (F/C)	Vin (V)	Iin (A)	Pin (W)	ATHD ≤%	PF ≥	CF ≤	BF ≥
Type	No.	Watts								
FC16T9	1	40	0/-18	120	0.58	40	150	0.5	1.7	0.88
FC12T9	1	32	0/-18	120	0.49	33	150	0.5	1.7	0.88

Note: Application and Performance Specification Information Subject to Change without Notification.

Performance

- Meets ANSI Standard C62.41-2002
- Meets FCC 18 CONSUMER Limits

Safety

- No PCB's
- UL & cUL listed (Class P, Type 1 Outdoor)
- OCV 300V
- **TYPE CC**

Application

- Maximum Ambient Temperature: 131°F, 55°C
- Sound Rated: A
- Maximum case temperature Tc: 167°F, 75°C

Physical Parameters

- Length 3.9" (98mm)
- Width 2.0" (51mm)
- Height 1.2" (30mm)
- Weight 0.6lbs

Lead Length

- White/Black 12 "± 1"
- Red/Blue 7 "± 1"

